



Nr	Ø	Długość (liczba)	Ø 8	Ø 12	Ø 16	Ø 20	Ø 28
Fundamenty							
15	28	304	110				334,40
16	16	868	28		243,04		
17	12	884	122	1078,48			
18	16	288	110		316,80		
19	12	101	76		76,76		304,08
20	20	181	168				
21	16	170	164		108,80		
Przyczółek z podparciem stałym przęśla							
22	20	322	22		70,84		
22A	20	353	31		109,43		
23	20	247	9		22,28		
24	20	348	10		34,80		
24A	20	379	10		37,90		
25	16	46	16		7,36		
26	12	844	34		286,96		
27	12	85	21		17,85		
28	12	120	3		3,60		
29	12	180	2		3,60		
30	12	40	3		3,20		
31	8	73	27	19,71			
32	16	760	8		60,80		
33	12	230	39		89,70		
34	12	143	51		72,99		
35	16	60	6		3,60		
Przyczółek z podparciem przesuwanym przęśla							
36	12	84	34		286,96		
31	8	73	27	19,71			
32	16	760	8		60,80		
33	12	230	39		89,70		
35	16	60	6		3,60		
36	20	192	39		74,88		
37	12	163	39		63,57		
38	12	78	39		30,42		
Skryżka na przyczółkach							
39	16	334	28		90,72		
39A	8	95	44	41,80			
40	16	484	20		86,80		
41	16	551	28		154,28		
42	16	236	32		75,52		
43	16	356	64		227,84		
44	12	122	56		68,32		
45	8	309	52	160,68			
46	8	52	76	39,52			
47	8	136	12	16,32			
48	12	95	32		30,72		
49	8	170	100	170,00			
50	8	146	100	146,00			
51	8	71	100	71,00			
Razem wg Ø							
Razem wg Ø 8							
Razem wg Ø 12							
Razem wg Ø 16							
Razem wg Ø 20							
Razem wg Ø 28							
Razem masa							
Łącznie							